



3 ROOF FRM'G. PLAN
SCALE: 1/4" = 1'-0"

SECTION 1/S-2

ROOF SKIRT;
SEE: LOFT FRAMING
PLAN

SIDE OF GAMBREL ROOF

G
S-2

NOTE: NO END RAFTER.
2X BLOCKING BETWEEN 2X6 OUTRIGGERS
SUPPORTED BY FRAMED ENDWALL.

2X6 OUTRIGGERS (ON EDGE)
SHOWN @ 48" O.C. MAX.

NOTE RAFTER SPACING:
PROVIDE FULL 16"
SPACE @ END.

ROOF SHEATHING:
7/16" O.S.B.
ROOF SHEATHING; APPLY PERPENDICULAR
TO RAFTER/TRUSS DIRECTION; STAGGER.
NAILING: 8d @ 6" O.C. @ EDGE &
8d @ 12" O.C. @ FIELD.

SLOPE BREAK

2X COLLAR TIES;
SEE SECTION.

ATTIC VENTILATION:
NEW BARN = 468 SQ.FT.;
PROVIDE 2 SQ.FT. OF
ATTIC VENTILATION (1/2 FROM
SCREENED SOFFIT VENTS & 1/2
SCREENED VENTS W/IN 3' VERTICAL
OF RIDGE, OR FROM ROOF VENTS).

2X FASCIA

2X6 OUTRIGGERS (ON EDGE) @ 48" O.C. MAX.
(SHOWN @ 30" O.C.); SEE DETAIL; G/S-2