



ELECTRICAL LEGEND

- ⊖ STANDARD SINGLE-POLE SWITCH
- ⊖^D RHEOSTAT/DIMMER SWITCH
- ⊖³ THREE-POSITION SWITCH
- ⊖⁴ FOUR-POSITION SWITCH
- ⊖^W WATERPROOF (OUTDOOR) SWITCH
- ⊖ STD. 110V DUPLEX OUTLET
- ⊖^Q QUAD 110V OUTLET
- ⊖^H "HALF-HOT" (SWITCHED) OUTLET
- ⊖^A ABOVE-COUNTER 110V DUPLEX OUTLET
- ⊖^{GFI} "GROUND FAULT INTERRUPTER"
- ⊖^{220V} 220V OUTLET (RANGE/OVEN/WELDING)
- ⊖^W WATERPROOF (EXTERIOR) 110V DUPLEX
- ⊖^F FLOOR-MOUNTED OUTLET
- ⊖^G GAS COCK (RANGE/OVEN/DRIER/WTR. HTR.)
- ⊖^D DISHWASHER OUTLET
- ⊖^I INCANDESCENT SURFACE-MT. CLG. FIXTURE
- ⊖^R RECESSED INCANDESCENT ("CAN-LIGHT")
- ⊖^{FLUOR} FLOURESCENT SURFACE MOUNT
- ⊖^{FLUOR} RECESSED FLOURESCENT
- ⊖^{FLUOR} MOUNTS BELOW KITCHEN UPPER CABINET
- ⊖^B FLOURESCENT BATHROOM FIXTURE
- ⊖^S WALL SCONCE
- ⊖^L EXTERIOR LIGHT
- ⊖^S EXTERIOR LIGHT (SPOT)
- ⊖^{SD} SMOKE DETECTOR (CLG.-MTD.)
- ⊖^{GR} GARBAGE GRINDER (SINK-MTD.; 110V)
- ⊖^H "HOSE BIB"
- ⊖^T THERMOSTAT
- ⊖^P PUSH-BUTTON (DOORBELL)
- ⊖^{OS} OCCUPANCY SENSOR
- ⊖^{MS} MOTION SENSOR

REMODEL ELECTRICAL FLOOR PLAN

1 SCALE: 1/4" = 1'-0"

NOTES:
 1) NO TYPICAL WALL OUTLET SHALL BE MORE THAN 15" ABOVE FINISHED FLOOR.
 2) NO WALL-MOUNTED LIGHT SWITCH SHALL BE MORE THAN 48" ABOVE FINISHED FLOOR.